

# Low pressure sanitizing agent sprayer

## Pressure from 2 to 8 Bar



Microspray

17.1



### TECHNICAL DETAILS

**Microspray** is a small high performance sanitizing agent sprayer .

Its stainless steel lance generates a special mist, making it ideal for disinfecting vertical surfaces and ceilings, with low consumption of sanitizing agent .

- ✓ Water flow: : 250 l/h (mean value)
- ✓ Water: From 2 to 8 bars (normally mains pressure is between 2 and 4 bars)
- ✓ Working temperature : 50°C Max
- ✓ Surface treated : About 25 m2 per minute
- ✓ Dimensions: 100x155x50 mm (L x H x P)
- ✓ Weight: 6 kg
- ✓ Material box: Stainless steel AISI/304
- ✓ Venturi system: Stainless steel AISI/316
- ✓ Product aspirated : from 0,1 % to 5 %

#### Whelled version:

- ✓ Stainless steel trolley
- ✓ S/s Pivoting front wheels ø 100 with brake
- ✓ Rear Wheels Ø 100 mm



Ø Foro Inc Ø Size Inc	Ø Foro mm Ø Size mm	Colore Color
No Hole Non forato		Trasparente Clear
0,01	0,25400	Rosa Pink
0,014	0,35560	Porpora Purple
0,018	0,45720	Azzurro Aqua
0,02	0,50800	Giallo Yellow
0,023	0,58420	Marrone Brown
0,025	0,63500	Arancione Orange
0,028	0,71120	Verde Green
0,035	0,88900	Bronzo Tan
0,04	1,01500	Blu Blue
0,043	1,09220	Bianco White
0,052	1,32080	Rosso Red

17.1



## STANDARD ACCESSORIES

- ✓ Stainless steel spray lance 600 mm complete of special nozzle
- ✓ Pvc gun resistant to impact and corrosion
- ✓ Antispot hose L= 20 mt
- ✓ N. 01 detergent suction hose L= 1,5 mt with filter
- ✓ Full screen printing illustration of the dosage in percentage
- ✓ Stainless steel hose holder
- ✓ Dosage regulator in Stainless steel with microperforated colorful inserts
- ✓ Microperforated colorful inserts kit to determinate the percentage of product aspirated

## AVAILABLE CONFIGURATION

CODE	WATER FLOW RATE (lt/h)	PRESSURE (Bar)	PERCENTAGE OF ASPIRED PRODUCT (%)	WEIGHT (Kg)	DIMENSIONS LxHxP (mm)	MAX TEMPERATURE IN-LET
15755	~250	2 ~ 8	0,1 ~ 5	6	100x155x50	50 °C

## AVAILABLE CONFIGURATION OF THE WHEELED VERSION

CODE	FOAM DISPENSER STATION	FLOW RATE (lt/h)	WATER PRESSURE (Bar)	WATER IN-LET MAX TEMPERATURE	PERCENTAGE OF ASPIRED PRODUCT (%)	WEIGHT (Kg)	DIMENSIONS LxHxD (mm)
30650	MICROSPRAY	~250	2 ~ 8	50 °C	0,1 ~ 5	25	580x1070x750