


ΚΑΜΠΥΛΗ 45°
 BEND 45° PE.
 COUDE 45° BL.
 CURVA 45° EL.


300 L



DN	A	C	D	R	gr
25	77,0	22,4	25,4	38,0	70
38	85,5	35,1	38,1	57,0	120
51	109,0	47,8	50,8	76,0	215
63	111,5	60,5	63,5	95,0	350
76	120,0	72,9	76,2	114,0	510
101	137,0	97,6	101,6	110,0	930
104	137,0	100,0	104,0	100,0	950

ΚΑΜΠΥΛΗ 90° ΚΟΝΤΗ
 BEND 90° WE.
 COUDE 90° BS.
 CURVA 90° ES.


310 S



DN	A	C	D	R	gr
25	38,0	22,4	25,4	38,0	45
38	57,0	35,1	38,1	57,0	115
51	76,0	47,8	50,8	76,0	200
63	95,0	60,5	63,5	95,0	320
76	114,0	72,9	76,2	114,0	510
101	100,0	97,6	101,6	110,0	810
104	110,0	100,0	104,0	100,0	850

ΚΑΜΠΥΛΗ 45° ΜΕ ΑΚΡΑ ΑΡΣ.-ΘΗΛ.
 BEND 45° MP/L. N. ED.
 COUDE 45° PF/PL. E. DN.
 CURVA 45° M./C. T. MD.


303 S



DN	A	B	C	F	gr
25	80,0	51,0	22,4	40-6	295
38	105,0	74,0	35,1	60-6	710
51	103,0	84,0	47,8	70-6	875
63	115,0	100,0	60,5	85-6	1.450
76	135,0	114,0	72,9	98-6	1.960
101	151,0	151,0	97,6	132-6	3.790

ΚΑΜΠΥΛΗ 90° ΑΚΡΑ ΑΡΣ.-ΘΗΛ.
 BEND 90° MP/L. N. WD.
 COUDE 90° PF/PL. E. SD.
 CURVA 90° M./C. T. SD.


313 S



DN	A	B	C	F	gr
25	55,0	55,0	22,4	40-6	250
38	70,0	70,0	35,1	60-6	650
51	82,0	82,0	47,8	70-6	780
63	105,0	105,0	60,5	85-6	1.265
76	110,0	110,0	72,9	98-6	1.775
101	150,0	150,0	97,6	132-6	3.080

ΚΑΜΠΥΛΗ 45° ΜΕ ΑΚΡΑ ΑΡΣΕΝΙΚΑ
 BEND 45° MP/MP ED.
 COUDE 45° PF/PF DN.
 CURVA 45° M./M. MD.


304 S



DN	A	C	F	gr
25	80,0	22,4	40-6	210
38	105,0	35,1	60-6	520
51	103,0	47,8	70-6	665
63	115,0	60,5	85-6	1.130
76	135,0	72,9	98-6	1.510
101	151,0	97,6	132-6	3.210

ΚΑΜΠΥΛΗ 90° ΜΕ ΑΚΡΑ ΑΡΣΕΝ.
 BEND 90° MP/MP WD.
 COUDE 90° PF/PF SD.
 CURVA 90° M./M. SD.

314 S



DN	A	C	F	gr
25	55,0	22,4	40-6	175
38	70,0	35,1	60-6	495
51	82,0	47,8	70-6	600
63	105,0	60,5	85-6	1.060
76	110,0	72,9	98-6	1.470
101	150,0	97,6	132-6	2.810